



HOTPLATES



Ceramic top hotplates “Ceramic-plac”

ADJUSTABLE HOT PLATE TEMPERATURE UP TO 400 °C. MAXIMUM SUPPORTABLE WEIGHT: 40 KG.

SAFETY

CONFORMS TO THE EN 61010 STANDARD, OVER TEMPERATURE CUT-OUT FITTED.

Excellent resistance to chemicals. Unaffected by thermal shock



Model part no. 3000920

Model part no. 3000921

Model part no. 3000919

FEATURES AND ADVANTAGES

The “CERAMIC-PLAC” has the following features and advantages:

- Flat, smooth surface.
- Excellent resistance to chemical agents.
- High heating power within the heated area that permits extreme temperature within a short heat up time.
- Excellent thermal qualities and penetration of infrared radiation.
- Easy to clean.

FEATURES

- External case of AISI 304 stainless steel.
- Heating elements mounted on ceramic fibre thus making an insulated compact block.
- Temperature energy control from 6 % to 70 % of nominal power. (Model Part No. 3000919 and 3000920).
- Hydraulic thermostat temperature control up to 400 °C (Model Part No. 3000921).

MODELS

Part No.	Heating Zones	Heating area in cm	Height / Width / Depth (exterior) cm	Power W	Weight Kg	Control system
3000919	1	18 Ø	10 28 33	1800	5.5	Energy controller
3000920	2	14 Ø + 14 x 14 ☒	10 27 47	2200	7.5	With individual energy controllers for each zone
3000921	1	30 x 30 ☒	10 49 49	3700	11	With hydraulic thermostat



Round Hotplates

HOTPLATE TEMPERATURE UP TO 400 °C. WITH 6 PLACE HEATING POWER CONTROLLER.

FEATURES

Cast steel plate with embedded heating elements throughout the plate surface.

Fast heating rate at maximum power setting.

Enamelled outer casing that is resistant to high temperatures and corrosive agents.

CONTROL PANEL

Controller 6 position power settings.



MODELS

Part No.	Plate Ø cm	Height / Width / Depth (exterior) cm			Power W	Weight Kg
1000718	12	8	20	20	1000	2.1
1000442	15	8	22	22	1600	3
1000443	19	8	26	26	2100	4.5



Hotplate - Circular "Selectemp"

ADJUSTABLE HOT PLATE TEMPERATURE FROM 45 °C TO 250 °C. STABILITY ± 2 °C.

FEATURES

Temperature control using a thermostat located in the center of the plate.

Non warping steel plate with embedded heating element throughout the plate's surface.

Enamelled outer casing, resistant to high temperatures and corrosive agents.

CONTROL PANEL

Hydraulic thermostat temperature control synchronised with an indicator lamp. 12 levels regulable button.

MODEL

Part No.	Plate Ø cm	Height / Width / Depth (exterior) cm			Power W	Weight Kg
1000444	15	8	22	22	1500	3



ACCESSORY

Circular sand, oil or water bath made of AISI 304 stainless steel, suitable for the "Selectemp" hotplate. Dimensions 200 mm dia x 115 mm high.

Comes complete with a lid with concentric reduction rings.

Part No. 7000008



Hotplate double circular "Duplac"

FOR PLATE TEMPERATURES UP TO 400 °C.

FEATURES

Hot plate with non warping cast steel plate with embedded heating elements throughout the hot plate surface.

Independent plate temperature control is maintained by pulsed energy controllers.

The exterior is epoxy covered steel.

CONTROL PANEL

Two temperature energy controllers.

Two indicator lamps function when the heaters are on.

MODEL

Part No.	Plate Ø cm	Height / Width / Depth (exterior) cm			Power W	Weight Kg
4000634	19	15	47	24	1900	8.5

